





Friction Materials & Phenolic Bearings

## **Gemini-GX Extruded Available for Shipment!**

March 31, 2015

Dear Customer,

Scan-Pac is pleased to announce that our new **Gemini-GX** extruded material is available for shipment. This material is offered in roll form in the sizes listed, and in addition to rolls we will also cut the material to various lengths to meet your specific needs. Request a price list and place your order today! Roll orders can ship within 24 hours.



**Gemini-GX** offers a high level of flexibility and low wear rate at .003 inch<sup>3</sup> /hp-hr. The new **Gemini-GX** also provides a stable coefficient of friction at .40. This material cures easily and can be bonded to brake shoes or disc brake pads. Typical applications include drum brakes on antique cars, brake bands, bonding segments for forklifts, industrial brakes and clutches, and centrifugal clutches.

All Gemini-GX roll sizes are listed on page two. If you have any questions, or would like to place an order for this material please contact one of our friendly and helpful customer service representatives.

Thanks and best regards,

Jeff Lichey VP, Sales & Marketing







## Friction Materials & Phenolic Bearings

## **Gemini-GX List of Available Roll Sizes**

Thickness	Width	Length (Feet)
1/8"	1"	34'
1/8"	1 ½"	34'
1/8"	4"	34'
1/8"	8 ½"	34'
5/32"	1 ½"	34'
3/16"	1"	34'
3/16"	1 ½"	34'
3/16"	2"	34'
3/16"	2 ½"	34'
3/16"	3"	34'
3/16"	3 ½"	34'
3/16"	4"	34'
3/16"	8 ½"	34'
1/4"	1 ½"	24 ½'
1/4"	2"	24 ½'
1/4"	3"	24 ½'
1/4"	3 ½"	24 ½'
1/4"	4"	24 ½'
1/4"	5"	24 ½'
1/4"	8 ½"	24 ½'
5/16"	3 ½"	16′
5/16"	7 ½"	16′
3/8"	2 ½"	16′
3/8"	3"	16′
3/8"	3 ½"	16′
3/8"	4"	16′
3/8"	5"	16′
3/8"	7"	16'